



International Filter Products

Revolutionary systems for your industry

JKP Series PTFE 0.45 µm/0.2 µm – Dual Layer Filter Capsule

JKP Capsule filter assemblies are ready-to-use filters that offer high flows, increased throughputs, high strength, all with the convenience and cleanliness of a disposable and easy-to-install filter assembly in a small package. These capsules are designed for small pre-filtration, clarification, and final filtration, in pharmaceutical, and biotechnological applications. The filtration shell is an all-polypropylene construction that provides excellent chemical compatibility, truly flexible, clean, and optimal. The filters are manufactured in accordance with GMP and comply with <USP 797> guidelines. The filters are flushed with pharmaceutical-grade purified pyrogens-free water, and 100% integrity tested prior to dispatch. Our filters and free from animal-derived components raw materials can be traced by Lot Number and strictly regulated maintaining ISO 13485 & ISO 14001 quality standards.

PureFlo® JKP - Series Filter Capsules



LFLM Connections

Inlet:

Luer Lock Female

Outlet:

Luer Lock Male



International Filter Products
Revolutionary systems for your industry



www.internationalfilterproducts.com

7914 Ajay Drive,
Sun Valley, California, 91352
Phone: 818-504-8115

Email: sales@internationalfilterproducts.com





International Filter Products

Revolutionary systems for your industry

Application

- Oil Base Solution
- Testosterone
- DMSO
- Low Flow Filtration
- Hormones
- Bio Bags Compatible
- Biologics
- Product Sterilization
- Alcohol Base Solution
- Pharmaceuticals
- Ketones
- Organic Solvent

Technical Data Sheet

Micron Rating:

Final Membrane: 0.2 μm PTFE [Sterilizing Grade Membrane]

Pre-Filter: Highly Asymmetric 0.45 μm PTFE

Effective Filtration Area:

Junior Capsule: 40.3 in^2 (260 cm^2)

Materials of Construction:

Membrane: Pharmaceutical Grade PTFE (Polytetrafluoroethylene) Sterilizing Grade

Membrane Feature: Hydrophobic, Chemically Inert, High Temperature Resistance

Shell, Cage, Core, End Caps: Polypropylene

Sealing: Thermally Bonded

Operating Conditions:

Maximum Operating Pressure: **Liquid:** 5.5 bar (80psi) at 72°F/22°C

Gas: 4.1 bar (60psi) at 72°F/22°C

Minimum Burst Pressure: 8.3 bar (120psi) at 72°F/22°C

Maximum Forward Differential Pressure: 5 bar (72 psi) at 72°F/22°C

Maximum Reverse Differential Pressure: 2.1 bar (30psi) at 72°F/22°C

Maximum Operating Temperature: 176°F/80°C



International Filter Products
Revolutionary systems for your industry



www.internationalfilterproducts.com

7914 Ajay Drive,
Sun Valley, California, 91352
Phone: 818-504-8115
Email: sales@internationalfilterproducts.com






International Filter Products

Revolutionary systems for your industry

Nominal Dimension:



Typical Filtered Volume:

2.2L – 9.6L [Oil base solution]

4.2L – 16.8L [Alcohol base solution]

*Volume Filtered is an estimated range for Pharmaceutical & Biological applications. The Filtration Volume is significantly influenced by your solution's viscosity, active ingredients, etc., properties. The best way to determine the exact filtration volume per filter is to try it with your solution.

Hold-Up Volume (Approx.):

Upstream Volume: 7.7 ml

Downstream Volume: 0.9 ml

Filter Integrity:

The finished product was sampled and shown to exhibit a minimum bubble point of ≥ 18 psi (1.2 bar) in 60%IPA / 40% water, and ≥ 17.5 psi (1.2 bar) in 70%IPA / 30% water.

Bacterial Retention ASTM F838-05:

The filters are quantitatively retentive towards *Brevundimonas diminuta* (ATCC #19146) at a minimum challenge level of 10^7 CFU per cm^2 of filtration area, consistent with ASTM F838-05



International Filter Products
Revolutionary systems for your industry



www.internationalfilterproducts.com

7914 Ajay Drive,
Sun Valley, California, 91352
Phone: 818-504-8115
Email: sales@internationalfilterproducts.com





International Filter Products

Revolutionary systems for your industry

Sterilization:

International Filter Products typically stocks ETO Sterilized [factory sterilized] filter capsules. Few sterilization methods are mentioned below:

Capsules can be autoclaved 25 times at 125 °C (257°F) for 30 minutes or chemically sanitized in situ using common sanitizing agents or hot water at 90 °C (194°F) for a limited time (dependent on time and temperature).

They can also be ETO sterilized, and the Ethylene Oxide (ETO) Sterilization Process must comply with ISO 10993-7:2008 Biological Evaluation of Medical Devices - Part 7. Each filter is subjected to a validated ETO process. Sterilization of the fluid path must be validated per ANSI/AAMI/ISO 11135 which provides a minimum sterility assurance level (SAL) of 10^{-6} .

Warning: The filters cannot be sterilized by steam-in-place (SIP) and Gamma Irradiation.

Regulatory Compliance 21CFR Part 177 & USP <88>:

The filters are constructed with polypropylene resins and filtration media in compliance with 21CFR Part 177 of the US Code of Federal Regulations and USP Class VI Biological USP <88>Test for Plastic.

USP <85> Bacterial Endotoxins:

The filters were tested to confirm that an aqueous extraction of this product contains <0.25 EU/ml as determined by the Limulus Amebocyte Lysate (LAL) Test

USP <645> Conductivity USP:

Effluent is tested during the manufacturing process and shown to meet the requirements for USP Sterile Water for Injection for conductivity.

USP <87> / ISO 10993-5 Cytotoxicity:

Extract from this product is non-Cytotoxic.

Hemolysis ASTM F756-17:

Extract from this product is non-Hemolytic.

Human and Veterinarian Use:

The product is safe for Human and Veterinarian use. CGMP CFR part 210 & 211, additional requirements of 21 CFR part 600 and 21 CFR part 680 are applicable to the aseptic manufacturing process.

Animal-Derived Components & TSE/BSE Risk:

No animal-derived material is intentionally added or used during the manufacture of this product.

Shelf Life:

The JKP capsules have a shelf life of 3 years from the date of sterilization.

Ethylene Oxide (ETO) Sterilized product packaging provides adequate protection to maintain a sterile barrier throughout the product's distribution, handling, and 3-year shelf life.



International Filter Products
Revolutionary systems for your industry



www.internationalfilterproducts.com

7914 Ajay Drive,
Sun Valley, California, 91352
Phone: 818-504-8115

Email: sales@internationalfilterproducts.com






International Filter Products

Revolutionary systems for your industry

JKP- Series PTFE Junior Capsules (Pharmaceutical Grade)

Ordering Guide



[1]	[2] Inlet and [3] Outlet	[4]
Micron Rating [Pre-Filter/Final Filter]	Inlet and Outlet Connection	Sterilization
F045020: Highly Asymmetric 0.45/0.2 µm Note: All final membranes are sterilizing grade.	- LF : Luer Lock Female - LM : Luer Lock Male	-ETO Ethylene Oxide Sterilization

Example:

JKPF045020LFLM- ETO

PureFlo® JKP Series Capsule, Dual Layer PTFE 0.45 µm Pre-Filter/0.2 µm PTFE Sterilizing Grade Hydrophobic Membrane, Effective Filtration Area 260 cm², Luer Lock Female Inlet, Luer Lock Male Outlet, Factory sterilized by ETO

Part Number

Description



International Filter Products
Revolutionary systems for your industry



www.internationalfilterproducts.com

7914 Ajay Drive,
Sun Valley, California, 91352
Phone: 818-504-8115
Email: sales@internationalfilterproducts.com





International Filter Products

Revolutionary systems for your industry

Special Configuration:

Layer Option:

- Dual Layer

Micron Rating Option:

- 0.04 Micron
- 0.1 Micron
- 0.2 Micron
- 0.45 Micron
- 0.65 Micron
- 0.8 Micron
- 1.2 Micron

Inlet Fitting Option:

- 1H : 1/8" Hose Barb
- 1Q : 1/8" Male Quick Coupling with Metal Latch
- 2H : 1/4" Hose Barb
- 2H-FB : 1/4" Hose Barb with Filling Bell
- 2Q : 1/4" Male Quick Coupling for Metal Latch
- 2N : 1/4" MNPT
- 3H : 3/8" Hose Barb
- LF : Luer Lock Female
- MT : 1/2" Tri-Clamp

Outlet Fitting Option:

- 1H : 1/8" Hose Barb
- 1Q : 1/8" Male Quick Coupling with Metal Latch
- 2H : 1/4" Hose Barb
- 2H-FB : 1/4" Hose Barb with Filling Bell
- 2Q : 1/4" Male Quick Coupling for Metal Latch
- 2N : 1/4" MNPT
- 3H : 3/8" Hose Barb
- LM : Luer Lock Male
- MT : 1/2" Tri-Clamp



International Filter Products
Revolutionary systems for your industry



www.internationalfilterproducts.com

7914 Ajay Drive,
Sun Valley, California, 91352
Phone: 818-504-8115
Email: sales@internationalfilterproducts.com

